

继电器系列特点：


1. 反应灵敏、产品结构稳定性高。
2. 使用寿命长、体积小等优点。
3. 可满足不同负载及环境下的使用。
4. 配套插座种类齐全，共有普通式、防护式、隔离式三大系列。

The Features of Relay Series :

1. Rapid response, high stability of product structure.
2. Long service life, small size and so on.
3. Product can be used in different load and environment.
4. Various matched socket, total 3 series: general, protection and isolation type.



Certificate	UL/CE
Contact type	2C/2CH 4C
Load current	5A/10A 5A
Contact resistance	50mΩ
Coil power	0.9W/1.2VA
Working temperature	-40~+70°C



Certificate	UL/CE
Contact type	2C/2CH 4C
Load current	5A/10A 5A
Contact resistance	50mΩ
Coil power	0.9W/1.2VA
Working temperature	-40~+70°C



Certificate	UL/CE
Contact type	2C 4C
Load current	5A 3A
Contact resistance	50mΩ
Coil power	0.9W/1.2VA
Working temperature	-25~+55°C




Certificate	UL/CE
Contact type	1C 2C
Load current	10A 5A
Contact resistance	50mΩ
Coil power	0.53W/1.0VA
Working temperature	-25~+55°C



Certificate	UL/CE
Contact type	2C
Load current	10A
Contact resistance	50mΩ
Coil power	2C:0.9W/1.2VA 4C:1.5W/3VA
Working temperature	-25~+55°C




Certificate	UL/CE
Contact type	4C
Load current	10A
Contact resistance	50mΩ
Coil power	2C:0.9W/1.2VA 4C:1.5W/3VA
Working temperature	-25~+55°C





Certificate	CE
Pin number	08 14
Rated current	10A 7A
Screw torque	1.0Nm
External connection wire	20-14/0.5-2.5AWG/mm ²
Working temperature	-40~+65°C



Certificate	CE
Pin number	08 14
Rated current	10A 10A
Screw torque	1.2Nm
External connection wire	20-14/0.5-2.5AWG/mm ²
Working temperature	-40~+65°C



Certificate	CE
Pin number	08 14
Rated current	10A 7A
Screw torque	1.0Nm
External connection wire	20-14/0.5-2.5AWG/mm ²
Working temperature	-40~+65°C



CE	690V/80A 16-6mm ²
UL	—
Poles	—



CE	690V/125A 35-16mm ²
UL	—
Poles	—



CE	690V/175A 70-16mm ²
UL	—
Poles	—



CE	690V/250A 120-35mm ²
UL	—
Poles	—




CE	690V/400A 185-35mm ²
UL	—
Poles	—



CE	690V/125A 35-16mm ²
UL	—
Poles	—



CE	690V/175A 70-16mm ²
UL	—
Poles	—



450V/750V	0.5-4.0mm ² 1.0-6.0mm ²
300V	24A,32A,41A,57A 2.5-15mm ² 6.0-16mm ²
UL	15A,20A,30A,50A 14-10,12-10AWG
Poles	2P-12P



450V/750V	0.5-2.5mm ² 0.5-4mm ²
300V	24A,32A,41A,57A 0.75-5mm ² 1.0-10mm ²
UL	15A,20A,30A,50A 20-14,16-12 14-10,12-10AWG
Poles	2P-12P



450V/24A	0.5-1.5mm ² (spring) 1.0-2.5mm ² (screw)
UL	300V/10A 22-16AWG
Poles	2P-12P



250V/6.3A	0.2-2.5mm ²
UL	300V/6.3A 22-14AWG
Poles	1P-5P



450V/24A	0.5-2.5mm ²
UL	600V/20A 22-12AWG
Poles	2P,3P,4P



CE	400V/24A 2.5mm ²
UL	300V/16A 18-12AWG
Poles	3P




CE	250V/24A 2.5mm ²
UL	300V/15A 22-14AWG
Poles	2P-24P



CE	250V/24A 2.5mm ²
UL	300V/15A 22-14AWG
Poles	2P-26P



CE	250V/24A 2.5mm ²
UL	300V/15A 22-14AWG
Poles	2P-24P



CE	250V/24A 2.5mm ²
UL	300V/15A 22-14AWG
Poles	2P-26P




CE	250V/24A 2.5mm ²
UL	300V/15A 22-14AWG
Poles	2P-24P



CE	250V/24A 2.5mm ²
UL	300V/15A 22-14AWG
Poles	2P-24P



CE	250V/24A 2.5mm ²
UL	300V/15A 22-14AWG
Poles	2P-26P




450V/24A	2.5mm ²
UL	300V/20A 22-12AWG
Poles	2P-24P



CE	450V/24A 2.5mm ²
UL	300V/20A 22-12AWG
Poles	2P-24P



CE	450V/24A 2.5mm ²
UL	300V/20A 22-12AWG
Poles	2P-26P



CE	450V/24A 2.5mm ²
UL	300V/20A 22-12AWG
Poles	2P-24P



CE	450V/24A 2.5mm ²
UL	300V/20A 22-12AWG
Poles	2P-26P



CE	450V/24A 2.5mm ²
UL	300V/20A 22-12AWG
Poles	2P-24P



CE	450V/24A 2.5mm ²
UL	300V/20A 22-12AWG
Poles	2P-24P



CE	450V/24A 2.5mm ²
UL	300V/20A 22-12AWG
Poles	2P-26P



750V/32A	4mm ²
UL	300V/25A 22-12AWG
Poles	2P-20P



CE	750V/32A 4mm ²
UL	300V/25A 22-12AWG
Poles	2P-20P